

CONSTRUCTION AND MATERIAL SPECIFICATIONS

Covering the proposed works of improvement for the following stream bank rehabilitation project:

Watershed: Little Sugar Creek

Site Location: Section 2, Township 21N, Range 32 W; Latitude 36.5740 N, Longitude 94.3581 W.

Specifications referred to herein shall form part of these Construction and Material Specifications and contractor should exercise special care to refer to them in request for quotations, in orders, and in subcontracts. Materials so specified shall conform to the technical requirements of the respective specifications referred to. Where used in these specifications, the terms Engineer, Contracting Officer, Contracting Officer's Representative and Contracting Officer's Technical Representative refer to project sponsor's personnel unless otherwise noted.

INDEX OF CONSTRUCTION SPECIFICATIONS

<u>Number</u>	<u>Title</u>	<u>Page</u>
002	Clearing and Grubbing	2
005	Pollution Control	5
224	Channel Excavation	9
227	Mobilization	11
240B	Seeding and Mulching	13
245	Rock Riprap	18

INDEX OF MATERIAL SPECIFICATIONS

<u>Number</u>	<u>Title</u>	<u>Page</u>
300C	Rock for Riprap	22

INDEX OF ANCILLARY ITEMS

<u>Number</u>	<u>Title</u>	<u>Page</u>
N/A	Stormwater Prevention Plan	24
N/A	Missouri Utility Locate Form	26



CONSTRUCTION SPECIFICATION

2. CLEARING AND GRUBBING

1. SCOPE

The work shall consist of the clearing and grubbing and disposal of trees, snags, logs, stumps, shrubs and rubbish from the designated areas.

2. PROTECTION OF EXISTING VEGETATION

Trees and other vegetation designated to remain undisturbed shall be protected from damage throughout the duration of the construction period. Any damages resulting from the contractor's operations or neglect shall be repaired by the contractor.

Earthfill, stockpiling of materials, vehicular parking, and excessive foot or vehicular traffic shall not be allowed within the drip line of vegetation designated to remain in place. Vegetation damaged by any of these or similar actions shall be replaced with viable vegetation of the same species, similar condition, and like size unless otherwise approved by the contracting officer.

Any cuts, skins, scrapes, or bruises to the bark of the vegetation shall be carefully trimmed and local nursery accepted procedures used to seal damaged bark.

Any limbs or branches 0.5 inch or larger in diameter that are broken, severed, or otherwise seriously damaged during construction shall be cut off at the base of the damaged limb or branch flush with the adjacent limb or tree trunk. All roots 1-inch or larger in diameter that are cut, broken, or otherwise severed during construction operations shall have the end smoothly cut perpendicular to the root. Roots exposed during excavation or other operations shall be covered with moist earth or backfilled as soon as possible to prevent the roots from drying out.

3. MARKING

The limits of the area(s) to be cleared and grubbed will be marked by stakes, flags, tree markings, or other suitable methods. Trees to be left standing and uninjured will be designated by special markings placed on the trunk about 6 feet above the ground surface.

4. CLEARING AND GRUBBING

All trees not marked for preservation and all snags, logs, brush, stumps, shrubs, rubbish, and similar materials shall be cleared from within the limits of the designated areas. Unless otherwise specified, all stumps, roots, and root clusters that have a diameter of 1 inch or larger shall be grubbed out to a depth of at least 2 feet below subgrade for concrete structures and 1 foot below the ground surface at embankment sites and other designated areas.

5 DISPOSAL

All materials cleared and grubbed from the designated areas shall be disposed of at locations shown on the drawings or in a manner specified in section 7. The contractor is responsible for complying with all local rules and regulations and the payment of any and all fees that may result from disposal at locations away from the project site.

6. MEASUREMENT AND PAYMENT

For items of work for which specific lump sum prices are established in the contract, payment for clearing and grubbing will be made at the contract lump sum price. Such payment shall constitute full compensation for all labor, equipment, tools and all other items necessary and incidental to completion of the work.

Compensation for any item of work described in the contract but not listed in the bid schedule will be included in the payment for the item of work to which it is made subsidiary. Such items and the items to which they are made subsidiary are identified in Section 7 of this specification.

7. ITEMS OF WORK AND CONSTRUCTION DETAILS

Items of work to be performed in conformance with this specification and the construction details therefore are:

a. Subsidiary Item, Clearing and Grubbing

- (1) This item shall consist of clearing and grubbing the stream channel as directed in the field by the government representative.
- (2) All timber removed from designated clearing and grubbing areas shall be burned or buried at a location directed in the field by the government representative.
- (3) This item of work will not be measured. No separate payment will be made for this item. Item is subsidiary to Bid Item #1, Rock Riprap.

CONSTRUCTION SPECIFICATION

5. POLLUTION CONTROL

1. SCOPE

The work shall consist of installing measures or performing work to control erosion and minimize the production of sediment and other pollutants to water and air from construction activities.

2. MATERIALS

All materials furnished shall meet the requirements of the Material Specifications listed in Section 8 of this specification.

3. EROSION AND SEDIMENT CONTROL MEASURES AND WORKS

The measures and works shall include, but are not limited to, the following:

Staging of Earthwork Activities The excavation and moving of soil materials shall be scheduled to minimize the size of areas disturbed and unprotected from erosion for the shortest reasonable time.

Seeding Seeding to protect disturbed areas shall occur as soon as reasonably possible following completion of that earthwork activity.

Mulching Mulching to provide temporary protection of soil surfaces from erosion.

Diversions Diversions to divert water from work areas and to collect water from work areas for treatment and safe disposition. These works are temporary and shall be removed and the area restored to its near original condition when they are no longer required or when permanent measures are installed.

Stream Crossings Culverts or bridges where equipment must cross streams. These works are temporary and shall be removed and the area restored to its near original condition when they are no longer required or when permanent measures are installed.

Sediment Basins Sediment basins to collect, settle and eliminate sediment from eroding areas from impacting properties and streams below the construction site(s). These basins are temporary and shall be removed and the area restored to its original condition when they are no longer required or when permanent measures are installed.

Sediment Filters Straw bale filters or geotextile sediment fences to trap sediment from areas of limited runoff. Sediment filters shall be properly anchored to prevent erosion under or around them. These works are temporary and shall be removed and the area restored to its original condition when they are no longer required or when permanent measures are installed.

Waterways Waterways for the safe disposal of runoff from fields, diversions and other structures or measures. These works are temporary and shall be removed and the area restored to its original condition when they are no longer required or when permanent measures are installed.

Other Additional protection measures as specified in Section 8 of this specification or required by Federal, State, or Local Government.

4. CHEMICAL POLLUTION

The Contractor shall provide water-tight tanks or barrels, or construct a sump sealed with plastic sheets to be used to dispose of chemical pollutants, such as drained lubricating or transmission fluids, grease, soaps, concrete mixer wash water, asphalt, etc., produced as a by-product of the construction activities. At the completion of the construction work, sumps shall be removed and the area restored to its original condition as specified in Section 8 of this specification. Sump removal shall be conducted without causing pollution.

Sanitary facilities such as chemical toilets, or septic tanks shall not be located adjacent to live streams, wells, or springs. They shall be located at a distance sufficient to prevent contamination of any water source. At the completion of construction activities, facilities shall be disposed of without causing pollution as specified in Section 8 of this specification.

5. AIR POLLUTION

The burning of brush and/or slash, and disposal of other materials shall adhere to state and local regulations.

Fire prevention measures shall be taken to prevent the start or spreading of wild fires which may result from project activities. Firebreaks or guards shall be constructed and maintained at locations shown on the drawings.

All public access or haul roads used by the contractor during construction of the project shall be sprinkled or otherwise treated to fully suppress dust. All dust control methods shall insure safe construction operations at all times. If chemical dust suppressants are applied, the material shall be a commercially available product specifically designed for dust suppression and the application shall follow manufacturer's requirements and recommendations. A copy of the product data sheet and manufacturer's recommended application procedures shall be provided to the Engineer five (5) working days prior to the first application.

6. MAINTENANCE, REMOVAL, AND RESTORATION

All pollution control measures and temporary works shall be adequately maintained in a functional condition for the duration of the construction period. All temporary measures shall be removed and the site restored to near original condition.

7. MEASUREMENT AND PAYMENT

Method 1 For items of work for which specific unit prices are established in the contract, each item will be measured to the nearest unit applicable. Payment for each item will be made at the contract unit price for that item. For water or chemical suppressant items used for dust control for which items of work are established in Section 8 of this specification, measurement for payment will not include water or chemical suppressants that are used inappropriately or excessive to need. Such payment will constitute full compensation for the completion of the work.

Method 2 For items of work for which lump sum prices are established in the contract, payment will be made as the work proceeds and supported by invoices presented by the Contractor that reflect actual costs. If the total of all progress payments is less than the lump sum contract price for this item, the balance remaining for this item will be included in the final contract payment. Payment of the lump sum contract price will constitute full compensation for completion of the work.

Method 3 For items of work for which lump sum prices are established in the contract, payment will be prorated and provided in equal amounts on each monthly progress payment estimate. The number of months used for prorating shall be the number estimated to complete the work as outlined in the Contractor's approved construction schedule. The final month's prorate amount will be provided with the final contract payment. Payment as described above will constitute full compensation for completion of the work.

All Methods The following provisions apply to all methods of measurement and payment. Compensation for any item of work described in the contract but not listed in the bid schedule will be included in the payment for the item of work to which it is made subsidiary. Such items, and the items to which they are made subsidiary, are identified in Section 8 of this specification.

8. ITEMS OF WORK AND CONSTRUCTION DETAILS

Items of work to be performed in conformance with this specification and the construction details therefore are:

a. Bid Item 3, Pollution Control

- (1) This item shall consist of scheduling of work, installing measures and performing work as needed to control erosion and minimize the production of sediment and other pollutants to the water and air during construction operations.

These temporary pollution control provisions contained herein shall be coordinated with other temporary and permanent pollution control features specified elsewhere in the contract or by state and local laws to assure effective pollution control.

- (2) All state and local laws governing pollution shall be followed.
- (3) The construction site shall be maintained in a clean and safe condition during construction operations.
- (4) Trash barrels shall be provided and utilized at the site. Trash shall be regularly collected and disposed of properly.
- (5) The contractor shall follow the Storm Water Pollution Prevention Plan (SWPPP) attached to the specifications. The Contractor shall post a copy of the plan in a location readily accessible by the public until construction activities are completed.
- (6) Restrict the clearing of timber and other vegetation to the absolute minimum required to accomplish the work. Work should be limited to one side of the channel.
- (7) Payment shall be by Method 2.

CONSTRUCTION SPECIFICATION

224. CHANNEL EXCAVATION

1. SCOPE

The work consists of removing sediment and debris from channel and the disposal of all excavated material.

2. EXCAVATION

The channel shall be excavated to the cross sections and grades shown on the plans. The excavated surfaces shall be reasonably smooth. The channel bank alignment shall be uniform.

3. DISPOSAL OF EXCAVATED MATERIALS

Material excavated from the channel shall be placed in spoil dikes as shown on plans. Spoil dikes shall be shaped reasonably smooth and shall be placed so surface water does not pond. Debris shall be separated from the soil materials, then burned, buried or otherwise disposed of at locations shown on the drawings or staked in the field.

4. MEASUREMENT AND PAYMENT

The quantity of this work will not be measured.

Payment for items of work listed in the bid schedule will be made at the specific lump sum prices established in the contract. Such payment will constitute full compensation for all labor, materials, equipment, and all other items necessary and incidental to the performance of the work.

5. ITEMS OF WORK AND CONSTRUCTION DETAILS

Items of work to be performed in conformance with this specification and the construction details therefore are:

a. Subsidiary Item, Channel Excavation

- (1) This item shall consist of removing all of the material required to construct the stream bank protection.
- (2) Excess spoil shall be placed within the work limits as indicated in the plans. Placement shall be at the top of the bank or other areas indicated in the plans. The exact placement of excavated material shall be approved in the field by the government representative.
- (3) No separate payment will be made for this item. Item is subsidiary to Bid Item #1, Rock Riprap.

CONSTRUCTION SPECIFICATION

227. Mobilization

1. SCOPE

The work consists of the cost of premiums paid for performance and payment bonds, if required, and the mobilization of the Contractor's forces and equipment necessary for performing the work required under the contract.

It shall include the transportation of personnel, equipment, and operating supplies to the site; establishment of offices, building, and other necessary facilities at the site; and other preparatory work at the site.

This item also includes demobilization, which is all activities and cost for transportation of personnel, equipment, and supplies not required or included in the contract from the site.

It shall not include mobilization for any specific item of work for which payment for mobilization is provided elsewhere in the contract.

2. PAYMENT

Payment for this item is made at the contract lump sum bid price.

3. ITEMS OF WORK AND CONSTRUCTION DETAILS

Items of work to be performed in conformance with this specification and the construction details therefore are:

a. Bid Item #2, Mobilization

- (1) This item shall consist of all mobilization and demobilization needed to perform all work.

CONSTRUCTION SPECIFICATION

240B. SEEDING AND MULCHING

1. SCOPE

The work shall consist of preparing the area for treatment and furnishing and placing seed, legume inoculant, mulch, fertilizer, and soil amendments as specified. The area to be seeded and mulched shall include the designated work area and other disturbed areas. The limits of the area will be marked on the ground.

2. MATERIAL

Seed - All seed shall conform to the current rules and regulations of the state of Missouri and all seed will be from the latest crop available. Seed shall be labeled in accordance with the state laws and the U.S. Department of Agriculture Rules and Regulations under the Federal Seed Act in effect on the date of invitations for bids. Bag tag figures will be evidence of purity and germination. No seed will be accepted with a test date of more than nine (9) months prior to the date of delivery to the site.

Seed that has become wet, moldy, or otherwise damaged in transit or storage will not be accepted. The percent of noxious weed seed allowable shall be as defined in the current state laws relating to agricultural seeds. Each type of seed shall be delivered in separate sealed containers and fully tagged unless an exception is granted in writing by the Contracting Officer.

Inoculation - All legume seeds such as ladino clover not pre-inoculated will be inoculated with the proper viable inoculant within 24 hours of planting. Pre-inoculated seed shall be planted prior to the expiration date of the inoculant tag or be re-inoculated with the appropriate inoculant within 24 hours prior to seeding. A sticker product will be used to adhere inoculant to the legume seeds.

Fertilizer - The fertilizer shall be a commercial grade fertilizer. The fertilizer shall meet the standard for grade and quality specified by state law. Where fertilizer is furnished from bulk storage, the contractor shall furnish a supplier's certification of analysis and weight. When required by the contract, a representative sample of the fertilizer shall be furnished to the Contracting Officer for chemical analysis.

Soil Amendments - Lime shall consist of standard ground agricultural limestone. Standard ground agricultural limestone is defined as ground limestone meeting current requirements of the State Department of Agriculture. Agricultural lime will be uniformly applied at a rate of 1500 pounds per acre of effective neutralizing material (ENM).

Mulch Material - Mulch shall consist of wheat, oat, or rye straw, or grass hay as approved by the Contracting Officer's Technical Representative. The mulch material shall be air dry, reasonably light in color, and shall not be musty, moldy, caked, or otherwise of low quality. The use of mulch that contains noxious weeds will not be permitted. The contractor shall provide a method satisfactory to the Contracting Officer's Technical Representative for determining the weight of mulch furnished.

Officer's Technical Representative or as shown on plans, mulch tackifiers, binders, mesh, or netting will be used to help anchor mulch materials.

7. **OVERSEEDING**

When overseeding into mulch is necessary, planting will occur during the next seeding period with minimal disturbance to the mulch. The seeding rates listed in Section 4 will be increased by 100 percent (doubled) when overseeding into mulch. Seed may be applied either by broadcast methods only December 16 through February 29 in the dormant seeding period or with a no-till drill during any of the seeding periods designated in Section 3. There will be no tillage or mechanical operation to cover broadcasted seed during an overseeding operation. Prior to overseeding into mulch cover, any existing competitive growth will be controlled with suitable herbicides.

Adequate mulch cover will be maintained to provide protection for the establishing seedlings.

8. **MEASUREMENT AND PAYMENT**

For items of work for which specific unit prices are established in the contract, each area treated as specified will be measured to the nearest 0.1 acre. Payment for treatment will be made at the contract unit price for the designated treatment which shall constitute full compensation for all materials, labor, equipment, tools, and other items necessary and incidental to the completion of the work.

3. **SEEDING MIXTURES AND DATES OF PLANTING**

Unless otherwise specified on the drawings, seed will be sown:

- ***Dormant Seeding Period*** from December 16 through February 29
- ***Spring Seeding Period*** from March 1 through May 15
- ***Summer Seeding Period*** from August 16 through September 15
- ***Fall Seeding Period*** from September 16 through October 15

From May 16 to August 15, a cool season grass and legume mixture may be seeded if there is adequate soil moisture to a depth of 18 inches at the time of planting. Adequate soil moisture shall be the minimum moisture content as defined in this specification.

Seeding will not be performed outside of the date ranges stated above. From October 16 to December 15 or drought periods between May 16 and August 15, all operations may be performed except sowing the seed.

Seed will be applied based on pounds of Pure Live Seed (PLS) per acre. Calculate PLS for each species and seed lot with the following formula:

$$\text{PLS (Pure Live Seed)} = \frac{\text{Purity}}{100} \times \frac{(\text{Germination} + \text{Hard Seed})}{100}$$

Calculate the total seed required per species on the following formula:

$$\text{Bulk Seed (lb.)} = \frac{\text{Seeding Rate (lb./ac.)} \times \text{Seeded Area marked on ground (ac.)}}{\text{PLS}}$$

4. **SEEDING RATES AND DATES FOR SOUTH MISSOURI: 1/**

Species	Mixture Seeding Rates (PLS) – Broadcast Seeding Methods Only			
	Dec 16 – May 15	May 16 – Aug 15	Aug 16 – Sept 15	Sept 16 – Oct 15
Tall Fescue	12.0 lb/ac	18.0 lb/ac	12.0 lb/ac	12.0 lb/ac
Redtop	1.3 lb/ac	2.0 lb/ac	1.3 lb/ac	1.3 lb/ac
Switchgrass <u>2/</u>	2.1 lb/ac	3.2 lb/ac		
Ladino Clover	0.9 lb/ac	1.4 lb/ac	0.9 lb/ac	
Orchardgrass			1.9 lb/ac	3.2 lb/ac

Species	Mixture Seeding Rates (PLS) – Drill Seeding Methods Only			
	Dec 16 – May 15	May 16 – Aug 15	Aug 16 – Sept 15	Sept 16 – Oct 15
Tall Fescue	8.0 lb/ac	12.0 lb/ac	8.0 lb/ac	8.0 lb/ac
Redtop	0.9 lb/ac	1.3 lb/ac	0.9 lb/ac	0.9 lb/ac
Switchgrass <u>2/</u>	1.4 lb/ac	2.1 lb/ac		
Ladino Clover	0.6 lb/ac	0.9 lb/ac	0.6 lb/ac	
Orchardgrass			1.3 lb/ac	2.1 lb/ac

1/ South Missouri counties are Bates, Henry, Benton, Morgan, Moniteau, Cole, Osage, Gasconade, Franklin, and St. Louis including those counties to the south of those listed.

2/ An improved cultivar of switchgrass will be required for these seedings. Approved switchgrass cultivars are “Cave-In-Rock”, “Blackwell”, “Alamo” (lowland sites only), and “Kanlow” (lowland sites only).

5. **FERTILIZING, SEEDBED PREPARATION, AND TREATMENT**

Disturbed areas will be treated with seed, mulch, fertilizer, and soil amendments as specified in this construction specification. Areas to be seeded shall be dressed to a reasonably smooth, firm surface.

Fertilizer furnishing the following minimum amounts of available plant nutrients per acre shall be applied.

	<u>All Areas</u>
Nitrogen (N)	30 lb./ac.
Phosphate (P ₂ O ₅)	90 lb./ac.
Potash (K ₂ O)	90 lb./ac.

Fertilizer shall be applied uniformly over the designated seeding area. Fertilizer and soil amendments shall be thoroughly incorporated into the upper 3 to 6 inches of soil within 24 hours after being applied.

The seedbed will be prepared with common farm implements such as disks, harrows and cultipackers. Alterations to the finished lines and grades of any structure caused by seedbed preparation shall be regraded by the contractor to meet the requirements of the applicable drawings and specifications prior to seeding.

The moisture content of the finished seedbed (upper 3-4 inches) must be adequate for germination. **Minimum moisture content** is present when the soil material will form a ball which does not readily separate when kneaded in the hand. **Maximum moisture content** is present when free water is evident on the surface of the kneaded soil ball. Areas not accessible to field machinery shall be prepared by hand. Parking areas shall be ripped or disked to a minimum depth of 6 inches prior to seedbed preparation.

If seeding is to be completed within 24 hours following construction, seedbed preparation may not be required unless soil conditions are compacted, polished or freshly cut areas.

Rocks larger than 6 inches in diameter, trash, weeds, woody materials, and other debris that will interfere with seeding or maintenance shall be removed or disposed of as directed by the Contracting Officer's Technical Representative.

Seedbed preparation shall be suspended when soil moisture conditions are not suitable for the preparation of a satisfactory seedbed as determined by the Contracting Officer's Technical Representative.

6. **SEEDING AND MULCHING**

All seeding operations shall be performed in such a manner that the seed is applied in the specified quantities uniformly on the designated areas. Prior to mulching, apply seed uniformly at a depth of 1/8 to 1/4 inch with a drill or cultipacker type of seeder - or - broadcast seed uniformly and immediately cover to a depth of 1/8 to 1/4 inch with a cultipacker or smooth wheel roller. Seeding operation shall be performed immediately after seedbed preparation, if seeding dates permit.

Mulch shall be applied uniformly to the designated areas at the rate of two tons per acre. Mulch shall be applied to the seeding areas not later than two (2) days after seeding has been performed. During the non-seeding periods mulch shall be applied within two (2) days after incorporation of fertilizer and soil amendments. An adequately weighted mulch tacker or crimper shall be used to anchor the mulch into the top one (1) inch of soil. On those areas too steep for safe operation if a mulch tacker or crimper, a non-asphalt tackifier will be applied with the straw mulch according to the manufacturer's recommendation in lieu of a mechanical operation. When required by the Contracting

9. ITEMS OF WORK AND CONSTRUCTION DETAILS

Items of work to be performed in conformance with this specification and construction details therefore are:

a. Subsidiary Item, Seeding and Mulching

1. This item shall consist of all work and materials needed to seed and mulch the disturbed areas.
2. Apply ground agricultural limestone and fertilizer uniformly as per soil test. In lieu of soil test information, the following application rates for fertilizer and lime will be used:
 - a. In lieu of the rate shown in Section 2 of this specification, apply ground lime at a rate of 1500 lbs./acre of effective neutralizing material (ENM).
 - b. In lieu of the rates shown in Section 5 of this specification, apply fertilizer uniformly over the designated seeding area at these rates:

Nitrogen (N)	60 pounds/acre
Phosphate (P ₂ O ₅)	90 pounds/acre
Potash (K ₂ O)	90 pounds/acre

3. Incorporate lime and fertilizer to a depth of at least 3” into the soil immediately after application during preparation of seedbed. All rills and gullies shall be filled and smoothed prior to application of lime and fertilizer.
4. In areas not accessible to or too small for practical use of field machinery, the seedbed shall be prepared by hand.
5. In lieu of the mixtures shown in Section 4 of this specification, seed shall be furnished in amounts that equal or exceed the following rate per acre:

Tall Fescue	32 Pounds (PLS)
Wheat	25 Pounds per acre

6. Mulch shall be small grain straw or grass hay relatively free of weed seed. The mulch shall be applied uniformly over the designated area at a rate of two tons per acre.
7. This item is subsidiary to Bid Item #1, Rock Riprap. No measurement of area seeded will be made for payment purposes.

CONSTRUCTION SPECIFICATION

245. ROCK RIPRAP

1. SCOPE

The work consists of the construction of rock riprap revetments and blankets, including filter, heavy filter fabric or bedding where specified.

2. MATERIALS

Rock riprap shall be obtained from the designated source or other approved source. It shall be free from dirt, clay, sand, rock fines and other materials not meeting the required gradation limits.

The size and grading of the rock shall be specified on the drawings.

Rock from designated sources shall be excavated, selected and processed as necessary to meet the quality and grading requirements as specified. The installed rock riprap shall conform to the specified grading limits.

Bedding aggregates when required, shall, unless otherwise specified, conform to the requirements for riprap.

Individual rock fragments for rock riprap and bedding shall be dense, sound and free from cracks, seams and other defects conducive to accelerated weathering. The rock fragments shall be angular to sub-rounded in shape. The least dimension of an individual rock fragment shall be not less than one-third the greatest dimension of the fragment.

Rock for riprap and bedding shall be sound, durable unweathered rock from approved sources.

Filter fabric when required, shall be of heavy duty non-woven materials of type specified on the drawings or otherwise approved.

3. SUBGRADE PREPARATION

The subgrade surfaces on which the rock riprap, filter, filter fabric or bedding is to be placed shall be cut or filled and graded to the lines and grades shown on the drawings. When earth fill to subgrade lines is required, it shall consist of approved materials and shall conform to the earthfill requirements.

Rock riprap, filter, filter fabric or bedding shall not be placed until the foundation is completed and the subgrade surfaces have been inspected and approved by the Engineer.

4. EQUIPMENT-PLACED ROCK RIPRAP

The rock riprap shall be placed by equipment on the surfaces and to the depths specified. The rock riprap shall be constructed to the full course thickness in one operation and in such a manner as to avoid serious displacement of the underlying materials. The rock riprap shall be delivered and placed in a manner that will insure that the riprap in place shall be reasonably homogeneous with the larger rocks uniformly distributed and firmly in contact one to another with the smaller rocks and spalls filling the voids between the larger rocks.

Rock riprap shall be placed in a manner to prevent damage to structures. Hand placing will be required to the extent necessary to prevent damage to the permanent works.

5. EQUIPMENT PLACED FILTER OR BEDDING

Bedding beneath riprap or filter shall be placed on the prepared subgrade surfaces as specified. Compaction of the filter or bedding aggregate will not be required, but the surface of such material shall be finished reasonably free of mounds, dips, or windrows.

6. MEASUREMENT AND PAYMENT

Method 1 - For items of work for which specific unit prices are established in the contract, the quantity of each type of rock riprap placed within the specified limits is computed to the nearest ton by actual weight. The volume of each type of filter or bedding aggregate is measured within the specified limits and computed to the nearest cubic yard by the method of average cross-sectional end areas. For each load of rock riprap placed as specified, the Contractor shall furnish to the Engineer a statement-of-delivery ticket showing the weight, to nearest 0.1 ton.

Payment will be made at the contract unit price for each type of rock riprap, filter or bedding. Such payment is considered full compensation for completion of the work.

Method 2 - For items of work for which specific unit prices are established in the contract, the quantity of each type of rock riprap placed within the specified limits is computed to the nearest 0.1-ton by actual weight. The quantity of each type of filter or bedding aggregate delivered and placed within the specified limits is computed to the nearest 0.1 ton. For each load of rock riprap placed as specified, the Contractor shall furnish to the Engineer a statement-of-delivery ticket showing the weight, to the nearest 0.1 ton. For each load of filter or bedding aggregate, the Contractor shall furnish to the Engineer a statement-of-delivery ticket showing the weight to the nearest 0.1 ton.

Payment will be made at the contract unit price for each type of rock riprap, filter or bedding. Such payment is considered full compensation for completion of the work.

Method 3 - For items of work for which specific unit prices are established by the contract, the volume of each type of rock riprap and filter or bedding aggregate will be measured within the specified limits and computed to the nearest cubic yard by the method of average cross-sectional end areas.

Payment will be made at the contract unit price for each type of rock riprap, filter or bedding. Such payment is considered full compensation for completion of the work.

Method 4 - For items of work for which specific unit prices are established by the contract, the volume of each type of rock riprap, including filter and bedding aggregate, will be measured within the specified limits and computed to the nearest cubic yard by the method of average cross-sectional end areas.

Payment will be made at the contract unit price for each type of rock riprap, including filter and bedding. Such payment is considered full compensation for completion of the work.

Method 5 - For items of work for which specific unit prices are established by the contract, the quantity of each type of rock riprap placed within the specified limits is computed to the nearest ton by actual weight. For each load of rock for riprap placed as specified, the Contractor shall furnish to the Engineer a statement-of-delivery ticket showing the weight to the nearest 0.1 ton.

Payment will be made at the contract unit price for each type of rock riprap, including geotextile used for filter or bedding. Such payment is considered full compensation for completion of the work.

Method 6 - For items of work for which specific unit prices are established by the contract, the volume of each type of rock riprap is measured within the specified limits and computed to the nearest cubic yard by the method of average cross-sectional end areas.

Payment will be made at the contract unit price for each type of rock riprap, including geotextile used for filter or bedding. Such payment is considered full compensation for completion of the work.

Method 7 - For items of work for which specific unit prices are not established by the contract, the quantity of rock shall not be measured.

Payment will be made at the contract lump sum price, including geotextile used for filter or bedding. Such payment is considered full compensation for completion of the work.

All Methods - The following provision apply to all methods of measurement and payment. Compensation for any item of work described in the contract but not listed in the bid schedule will be included in the payment for the item of work to which it is made subsidiary. Such items and the items to which they are made subsidiary are identified in Section 7.

No separate payment will be made for testing the gradation of the test pile. Compensation for testing is included in the appropriate bid item for riprap.

7. ITEMS OF WORK AND CONSTRUCTION DETAILS

Items of work to be performed in conformance with this specification and the construction details therefore are:

a) Bid Item #1, Rock Riprap

- 1) This item shall consist of furnishing and placing rock riprap to construct stream barbs and bank protection in the stream channel and stream bank as shown on the drawings.
- 2) The source of the rock riprap shall be approved by the Government Representative prior to delivering the rock to the project location.
- 3) The Contractor shall provide a representative gradation pile of rock at the rock source location and at the project location. The size of the gradation pile shall be a minimum of two (2) tons. The length and width of each rock shall be individually measured along with the weight of each rock. The Contractor shall provide the Government Representative a copy of all of the weights and measurements of the rock in order to determine if the rock conforms to the gradation as listed on the plans.
- 4) The gradation of the rock riprap for the stream barbs shall meet the gradation table requirements as shown on the plans. The Contractor shall use riprap that meets Missouri Standard Specifications for Highway Construction requirements for Type 4 rock ditch liner (or the gradation table on the plans) for the rock riprap that will be placed for the stream bank protection as shown on the plans.
- 5) The rock shall be equipment placed.
- 6) The channel shall be excavated as common excavation, and to the cross sections and grades shown on the plans to place the rock riprap. The excavated surfaces shall be reasonably smooth. This work is subsidiary to Bid Item #1, Rock Riprap. No separate payment will be made for this work.
- 7) Use clean, uncontaminated materials for fill in order to minimize excessive turbidity by leaching of fines, as well as to preclude the entrance of deleterious and/or toxic materials into the waters of the United States by natural runoff or by leaching.
- 8) Measurement and Payment shall be by Method 7 as stated in Section 6 of this specification.
- 9) Items of work subsidiary to this bid item are:
 - a). Clearing and Grubbing – Construction Specification 002.
 - b). Channel Excavation – Construction Specification 224.
 - c). Seeding and Mulching – Construction Specification 440B.

MATERIAL SPECIFICATION

300C. ROCK FOR RIPRAP

1. SCOPE

This specification covers the quality of rock to be used in the construction of rock riprap.

2. QUALITY

Individual rock fragments shall be dense, sound and free from cracks, seams and other defects conducive to accelerated weathering. Except as otherwise specified the rock fragments shall be angular to subrounded in shape. The least dimension of an individual rock fragment shall be not less than one-third the greatest dimension of the fragment.

Except as otherwise provided, the rock shall be tested and shall have the following properties:

- a. Bulk Specific Gravity (saturated surface-dry basis): Not less than 2.5 when tested in accordance with ASTM Method C 127 on samples prepared as described for soundness testing.
- b. Absorption: Not more than 2 percent when tested in accordance with ASTM Method C 127 on samples prepared as described for soundness testing.
- c. Soundness: The weight loss in 5 cycles shall be not more than 10 percent when sodium sulfate is used or more than 15 percent when magnesium sulfate is used when tested in accordance with ASTM Method C 88 for coarse aggregate modified as follows:

The test sample shall consist of 5000 ± 300 grams of rock fragments, reasonably uniform in size and cubical in shape and weighing, after sawing, approximately 100 grams each. They shall be obtained from rock samples that are representative of the total rock mass, as noted in ASTM Practice D 4992, and that have been sawed into slabs as described in ASTM Practice D 5121. The samples shall further be reduced in size by sawing the slabs into cubical blocks. The thickness of the slabs and the size of the sawed fragments shall be determined by the size of the available test apparatus and as necessary to provide, after sawing, the approximate 100 gram samples.

Due to internal defects, some of the cubes may break during the sawing process or during the initial soaking period. Do not test any of the cubes that break during these preparatory processes. Such breakage, including an approximation of the percentage of cubes that break, shall be noted in the report.

After the sample has been dried, following completion of the final test cycle and washed to remove the sodium sulfate or magnesium sulfate, the loss of weight shall be determined by subtracting from the original weight of the sample the final weight of all fragments which have not broken into three or more pieces.

The report shall show the percentage loss of the weight and the results of the qualitative examination.

- d. **Rock Slab Soundness:** When specified, the rock shall also be tested in accordance with ASTM D 5240, Standard Test Method for Testing Rock Slabs to Evaluate Soundness of Riprap by Use of Sodium Sulfate or Magnesium Sulfate. Unless otherwise specified, the average percent weight loss shall not exceed 20 percent when sodium sulfate is used or 25 percent when magnesium sulfate is used.

Rock that fails to meet the requirements stated above in a, b, c, or d (if specified), may be accepted only if similar rock from the same source has been demonstrated to be sound after 5 years or more of service under conditions of weather, wetting and drying, and erosive forces similar to those anticipated for the rock to be installed under this specification.

3. GRADING

The rock shall conform to the specified grading limits after it has been placed in the riprap.

STORM WATER POLLUTION PREVENTION PLAN

DSR 119-15-001 Little Sugar Creek
Emergency Watershed Protection

05/15
McDonald County, Missouri

Description of Best Management Practices (BMP's)

One or more of the following temporary or permanent BMP's may be installed or practiced on the site. Other practices not listed may be used during the course of construction if deemed necessary by NRCS in order to comply with permit requirements.

Protective Dikes (5)	Sediment Basins (5)
Seeding/Mulching (240)	Silt Fence (5)
Straw Bale Filters (5)	Temporary Mulching (5)
Grass-lined Channels (5)	Rip Rap Channels (245)
Diversions (5)	Grass Filter Strips (5)

Disturbed Areas

Work areas sites are shown on the plans. Disturbed areas will be re-vegetated by seeding after construction is completed.

Temporary and Permanent Non-Structural BMP's

1. Staging of activities -- Stripping, clearing, grubbing and earthwork activities will be staged.
2. Seeding and mulching -- Seeding and mulching will be installed on designated disturbed areas only as needed in accordance with Construction Specifications as soon as possible after construction activity on the areas is completed.

Inspection

The Contracting Organization will inspect the construction site at least once every 14 days during periods of construction activity to ensure all installed BMP's and other pollution control measures are properly installed, operating and maintained. In addition, the Contracting Organization will conduct a site inspection within 72 hours following heavy rains provided the disturbed areas have not been finally stabilized with permanent BMP's and vegetation. Any deficiencies found during inspections will be corrected within seven calendar days. The Contracting Organization will promptly notify the site contractor responsible for operation and maintenance of the BMP's of any deficiencies.

Reporting of Other Discharges

1. Hazardous Substance and Oil Spill Reporting (Refer to the general permit).
2. Removed Substances (Refer to the general permit).
3. Change in discharge: In the event soil contamination or hazardous substances are discovered at the site during land disturbance activities, NRCS will notify MDNR in writing.

Amendments

This SWPPP will be amended and updated during the term of the land disturbance activity when:

- a. Design, operation, or maintenance requirements of BMP's is changed;
- b. Design of the construction project is changed in a manner that could significantly affect the quality of the storm water discharges;
- c. NRCS inspections indicate deficiencies in the SWPPP or any BMP;
- d. MDNR notifies NRCS of deficiencies in the SWPPP;
- e. The SWPPP is determined to be ineffective in significantly minimizing or controlling erosion and sedimentation (e.g., there is visual evidence, such as excessive sediment deposits in streams or channels);
- f. Total Settleable Solids from storm water outfall exceed 2.5 ml/L/hr; or
- g. MDNR determines violations of Water Quality Standards may occur or have occurred.

Records

Records including all amendments, results of any monitoring and analysis, and all site inspection records will be kept by the project sponsor until the construction contract for the site is completed and closed.

Sender's Name (first & last): _____ email: _____

Company Name: _____ Phone #: (____) _____

Fax #: (____) _____ Contact Name: _____

Contact#: (____) _____ Recording device? YES NO UNKNOWN

Excavator Name: _____

Excavator Address: _____ Phone #: (____) _____

Type of work: _____ Type of equipment: _____

Work being done for: _____

Tunneling? (Circle one)	YES	NO	UNKNOWN	
Horizontal Boring? (Circle one)	YES	NO	UNKNOWN	Depth: _____
Explosives? (Circle one)	YES	NO	UNKNOWN	

County: McDonald Town: _____

Is Entire Job Inside Town Boundaries? (Circle one) YES NO (If "No" please provide driving directions)

Address Number(s): _____ Dig Street: _____

Nearest Street Intersecting Dig Street: _____

Is Entire Job within 1 block of intersection? (Circle one) YES NO

If not, then how far? (Circle one) 1/8mi 1/4mi 1/2mi 3/4mi 1mi Direction: N S E W

What side(s) of the road is the work on? (Circle) N S E W

If the site is outside of the town boundaries,
how far off the road will cover the entire job? _____ (List a measurable distance - Ft, Yds)

Location of Work: (Be specific, where on property-Include driving directions if necessary) _____

Start Date/Time: _____ or ROUTINE (Circle "Routine" or list a start date and time of 8:00 a.m. or later on the 3rd business day)

TWP: 21 N RANGE: 32 (Circle one) E or **(W)** SEC: 2 QS: _____

*Call to set meeting? (Circle one) YES NO Mark lines at meeting? (Circle one) YES NO

*NAD 83 LAT: 36.5740 LON: 94.3581

All fields except those marked with an asterisk (*) need to be completed or your fax will be returned. This will delay your locates!

Missouri One Call System Use Only

Issued Ticket # : _____ Operator: _____
Page 26 of 26